



RECEIVER

RCV BMS-1

THE SAFE CONNECTION TO THE MACHINE



RECEIVER

+ EASY AND QUICK CONFIGURE

The majority of ABITRON's receivers have a modular structure, which brings some great benefits to your application: The receivers can be equipped quickly, cost-optimised and adapted to your application. In the event that your device is in need of repair, the modules can be replaced by our service staff in an instant, reducing downtime to an absolute minimum.








RCV BMS-1 RECEIVER VERSION

Proven variant in the HS-2 housing

The receiver BMS-1 is first choice for the control of current and voltage controlled hydraulic valves. The receiver BMS-1 is characterized by its modular design and is therefore the perfect support in mobile vehicle technology.

INTERFACES:	1 STOP-output (up to Kat.3 Pld / SIL3) ($\leq 7,5A @ 30V DC1$) 12 relay outputs ($\leq 4A @ 250V$ & 50%ED S2 60s) 6 analogue outputs (VC or PWM)
PROTECTION CLASS:	IP 65
TEMPERATURE RANGE:	-25 to +70° C
WEIGHT:	approx. 2500 g
DIMENSIONS:	245 x 165 x 90 mm
FREQUENCY RANGE:	419/429/432-481/863-930 MHz, 2.4GHz
OPERATING VOLTAGE:	8 - 30 VDC

 INDUSTRY	 CONSTRUCTION	 HYDRAULIC	 SPECIAL VEHICLE	 CUSTOMISED
---	---	--	--	---