



RECEIVER

RCV CBB-1

THE SAFE CONNECTION TO THE MACHINE



RECEIVER

+ EASY AND QUICK TO CONFIGURE

The majority of ABITRON's receivers have a modular structure, which brings some great benefits to your application: The receivers can be equipped quickly, cost-optimised and adapted to your application. In the event that your device is in need of repair, the modules can be replaced by our service staff in an instant, reducing downtime to an absolute minimum.




RCV CBB-1 NEW RECEIVER GENERATION

Analogue and digital inputs with easy pairing

The RCV CBB-1 is the latest generation of compact interface receivers. This newly developed technology offers a variety of possibilities, such as two separate CAN interfaces, analogue and digital inputs and easy pairing.

INTERFACES:	2 STOP-relay (up to Kat. 3 Ple / SIL3) 32V DC1 ≤4A @ 100%ED CANopen, CANopen Safety, J1939, Industrial Ethernet
PROTECTION CLASS:	IP 65
TEMPERATURE RANGE:	-25 to +70° C
WEIGHT:	approx. 800g
DIMENSIONS:	165 x 115 x 65 mm
FREQUENCY RANGE:	223MHz – 930MHz, 2.4GHz
OPERATING VOLTAGE:	8 - 30 VDC

 INDUSTRY	 CONSTRUCTION	 HYDRAULIC	 SPECIAL VEHICLE	 CUSTOMISED
---	---	--	--	---