



RECEIVER

RCV 14+

THE SAFE CONNECTION TO THE MACHINE



RECEIVER

+ EASY AND QUICK CONFIGURE

The majority of ABITRON's receivers have a modular structure, which brings some great benefits to your application: The receivers can be equipped quickly, cost-optimised and adapted to your application. In the event that your device is in need of repair, the modules can be replaced by our service staff in an instant, reducing downtime to an absolute minimum.





RCV 14+ RECEIVER VERSION

Standard receiver

The RCV 14+ is a standard receiver with 14 output relays. It can be equipped with twelve additional output relays or a module for proportional controls on demand. Due to the modular design, it can be easily and quickly be configured for many requirements of applications in industry and construction.

INTERFACES:	2 STOP-relay (up to Kat.3 Pld / SIL3) 250V AC1 / 32V DC1 ≤4A @ 100%ED 14 relay outputs 250V AC1 / 32V DC1 ≤4A @ 50%ED 30s/30s ≤2A @ 100%ED
PROTECTION CLASS:	IP 65
TEMPERATURE RANGE:	-25 to +70° C in DC-version -20 to +50° C in AC-version
WEIGHT:	approx. 1800 g
DIMENSIONS:	245 x 165 x 90 mm
FREQUENCY RANGE:	419/429/432-481/863-930 MHz, 2.4GHz
OPERATING VOLTAGE:	depending on the version 10-30 VDC (±10%) 48/115/230 VAC (±10% 50-60Hz)

 INDUSTRY	 CONSTRUCTION	 HYDRAULIC	 SPECIAL VEHICLE	 CUSTOMISED
---	---	--	--	---