



RECEIVER

# RCV 26+

## THE SAFE CONNECTION TO THE MACHINE



ABITRON

# RECEIVER

## + EASY AND QUICK CONFIGURE

The majority of ABITRON's receivers have a modular structure, which brings some great benefits to your application: The receivers can be equipped quickly, cost-optimised and adapted to your application. In the event that your device is in need of repair, the modules can be replaced by our service staff in an instant, reducing downtime to an absolute minimum.








## RCV 26+ RECEIVER VERSION

### Standard receiver

The RCV 26+ is a standard receiver with 26 output relays. Due to its modular design, it can be easily and quickly configured for many industrial and construction applications.

<b>INTERFACES:</b>	2 STOP-relay (up to Kat.3 Pld / SIL3) 250V AC1 / 32V DC1 ≤4A @ 100%ED 26 relay outputs 250V AC1 / 32V DC1 ≤4A @ 50%ED 30s/30s ≤2A @ 100%ED
<b>PROTECTION CLASS:</b>	IP 65
<b>TEMPERATURE RANGE:</b>	-25 to +70° C in DC-version -20 to +50° C in AC-version
<b>WEIGHT:</b>	approx. 2000 g
<b>DIMENSIONS:</b>	245 x 165 x 90 mm
<b>FREQUENCY RANGE:</b>	419/429/432-481/863-930 MHz, 2.4GHz
<b>OPERATING VOLTAGE:</b>	depending on the version 10-30 VDC (±10%) 48/115/230 VAC (±10% 50-60Hz)

 INDUSTRY	 CONSTRUCTION	 HYDRAULIC	 SPECIAL VEHICLE	 CUSTOMISED
---	---	--	--	---